

STARTECH .com 2S1P PCI Express Schnittstellenkarte - PCIe 2x



✓ Stock

CHF **84.00**

CHF **77.71** excl.

StarTech.com 2S1P PCI Express Schnittstellenkarte - PCIe 2x Seriell DB9 / 1x Parallel DB25 Karte mit Breakout Kabel - Adapter Parallel/Seriell - PCIe Low-Profile - RS-232 - 2 Anschlüsse + 1 paralleler Port

Manufacturer [STARTECH](#)
EAN 65030842426
Manufacturer# PEX2S1P553B
Tagged as 

Description

Add a parallel port and two RS-232 serial ports to your PC through a PCI-Express expansion slot. The PEX2S1P553B 2S1P PCI Express Serial Parallel Combo Card with Breakout Cable combines the functionality of Parallel and Serial cards, adding 2 RS232 serial ports and 1 parallel port through a single PCI Express (PCIe) slot. Suitable for almost any computer, the card offers a low profile/half-height design and includes an optional full-height bracket. The included break-out cable uses a single connector on the card to deliver 3 ports, avoiding crowded connections that can occur with fixed/static ports. Compatible with a broad range of operating systems including DOS, Windows? 7/Server 2008 R2/Vista/XP/Server 2003/2000/98SE (32/64 bit), Linux and Mac OS X. The card also features a native single-chip design that provides improved speed and reliability while reducing the CPU load by as much as 48% over conventional (bridge chip) cards.

Specification

Product Description	StarTech.com 2S1P PCI Express Serial Parallel Combo Card with Breakout Cable - parallel/serial adapter - PCIe - 2 ports
Device Type	Parallel/serial adapter
Form Factor	Plug-in card - low profile
Interface (Bus) Type	PCI Express x1
Dimensions (WxDxH)	2.3 cm x 9.5 cm x 7.9 cm

Weight	50 g
Ports Qty	2 ports
Auxiliary Ports	1 x parallel port
Data Link Protocol	RS-232
System Requirements	Microsoft DOS, Linux, Microsoft Windows 95/98 Second Edition, Microsoft Windows Server 2003, Apple MacOS X 10.4 or later, Microsoft Windows Server 2008 R2, Microsoft Windows 2000/XP/Vista/7
Manufacturer Warranty	Limited lifetime warranty

Techn. Details

Device Type	Parallel/serial adapter - 2 ports
Form Factor	Plug-in card - low profile
Interface (Bus) Type	PCI Express x1
Connectivity Technology	Wired
Data Link Protocol	RS-232
Auxiliary Ports	1 x parallel port
Interfaces	1 x IEEE 1284 (EPP/ECP) - 25 pin D-Sub (DB-25) (on cable) 2 x RS-232 - 9 pin D-Sub (DB-9) (on cable)
Compatible Slots	1 x PCI Express x1 - low-profile
Included Accessories	Full-height bracket
Cables Included	1 x serial / parallel cable (external)
Compliant Standards	WHQL, RoHS
OS Required	Microsoft DOS, Linux, Microsoft Windows 95/98 Second Edition, Microsoft Windows Server 2003, Apple MacOS X 10.4 or later, Microsoft Windows Server 2008 R2, Microsoft Windows 2000/XP/Vista/7

Width	2.3 cm
Depth	9.5 cm
Height	7.9 cm
Weight	50 g
Service & Support	Limited warranty - lifetime
Min Operating Temperature	0 °C
Max Operating Temperature	70 °C
Humidity Range Operating	5 - 85%

Date added: 2023-02-23 08:32:04 / SID: 4950943 / DID: V932027