

LevelOne - FPS-1032



✓ Stock

CHF **124.00**

CHF **114.71** excl.

LevelOne FPS-1032 - Print server - USB 2.0 - 10/100 Ethernet

Manufacturer [LevelOne](#)

EAN 4015867142233

Manufacturer# 501032

Tagged as [New](#)

Description

Systemvoraussetzungen

- MS Windows ME, 2000, XP, Vista
- Mac OS 8.1 oder höher
- Unix/Linux
- Netware (Bindery/ NDS)

Dimensionen

Breite	64.7 mm
Tiefe	73.2 mm
Höhe	28.4 mm
Gewicht	58 g

Schnittstellen

Übertragungsart	LAN (100MB)
Anzahl Ports	1
Schnittstellen	USB 2.0 RJ-45 (100Mbps)

Software

Kompatible Betriebssysteme	Windows 7
	Windows 8
	Windows 10
	Windows Vista
	Windows XP (und neuer)
	Windows 2000 (und neuer)
	Mac OS 8.1
	UNIX
	Linux
	Netware 3.12 (oder höher)

Specification

Product Description	LevelOne FPS-1032 - print server - USB 2.0 - 10/100 Ethernet
Device Type	Print server
Form Factor	External
Interface (Bus) Type	USB 2.0
Ports	10/100 Ethernet
Dimensions (WxDxH)	7.3 cm x 2.8 cm x 6.5 cm
Weight	56 g
Cabling Type	Ethernet 10Base-T, Ethernet 100Base-TX
Data Link Protocol	10Mb LAN, 100Mb LAN
Data Transfer Rate	100 Mbps
Network / Transport Protocol	TCP/IP, AppleTalk, NetBEUI/NetBIOS, IP/IPX, LPR/LPD
Compliant Standards	IEEE 802.3, IEEE 802.3u
System Requirements	UNIX, Apple MacOS, Novell NetWare, Linux, Microsoft Windows 2000, Microsoft Windows Millennium Edition, Microsoft Windows XP, Microsoft Windows Vista

Techn. Details

Device Type	Print server
-------------	--------------

Form Factor	External
Interface (Bus) Type	USB 2.0
Ports	10/100 Ethernet
Connectivity Technology	Wired
Cabling Type	Ethernet 10Base-T, Ethernet 100Base-TX
Data Link Protocol	Ethernet, Fast Ethernet
Data Transfer Rate	100 Mbps
Network / Transport Protocol	TCP/IP, AppleTalk, NetBEUI/NetBIOS, IP/IPX, LPR/LPD
Remote Management Protocol	SNMP, IPP
Status Indicators	Power, status, link/activity
Features	Auto-sensing per device, DHCP support, manageable
Compliant Standards	IEEE 802.3, IEEE 802.3u
Interfaces	1 x 100Base-TX - RJ-45
Connections	1 x USB 2.0 - 4 pin USB Type A
Compliant Standards	FCC Class B certified
Power Device	Power adapter - external
OS Required	UNIX, Apple MacOS, Novell NetWare, Linux, Microsoft Windows 2000, Microsoft Windows Millennium Edition, Microsoft Windows XP, Microsoft Windows Vista
Width	7.3 cm
Depth	2.8 cm
Height	6.5 cm
Weight	56 g
Min Operating Temperature	0 °C

Max Operating 50 °C
Temperature

Humidity Range 0 - 70%
Operating

Date added: 2018-10-07 08:19:15 / SID: 3367361 / DID: 86169