

D-Link 7-PORT UNMANAGED SWITCH 5X1G 2X2.5G FANLESS NMS IN CPNT



Delivery date unknown

CHF **146.00**

CHF **135.06** excl.

7-PORT UNMANAGED SWITCH 5X1G 2X2.5G FANLESS NMS IN CPNT

Manufacturer

[D-Link](#)

EAN

0790069470240

Manufacturer#

DMS-107/E

Tagged as

New

Description

7-Port Multi-Gigabit Unmanaged Switch

Specification

Product	D-Link DMS 107 - switch - 7 ports - unmanaged
Description	
Device Type	Switch - 7 ports - unmanaged
Subtype	Gigabit Ethernet
Ports	5 x 10/100/1000 + 2 x 2.5GBase-T
Performance	Switching capacity: 20 Gbps Packet forwarding rate: 14.88 Mpps
Capacity	Packet buffer size: 2 MB
MAC Address Table Size	2K entries
Jumbo Frame Support	9216 bytes

Features	Flow control, auto-sensing per device, auto-negotiation, auto-uplink (auto MDI/MDI-X), store and forward, Link Fault Detection, QoS, D-Link Green Technology, fanless, metal housing, EEE, auto firmware update
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3az, IEEE 802.3bz
Dimensions (WxDxH)	14.5 cm x 8.2 cm x 2.8 cm
Weight	295.2 g
Localisation	Europe
Manufacturer Warranty	2-year warranty

Techn. Details

Device Type	Switch - 7 ports - unmanaged
Enclosure Type	Desktop, wall-mountable
Subtype	Gigabit Ethernet
Ports	5 x 10/100/1000 + 2 x 2.5GBase-T
Performance	Switching capacity: 20 Gbps Packet forwarding rate: 14.88 Mpps
Capacity	Packet buffer size: 2 MB
MAC Address Table Size	2K entries
Jumbo Frame Support	9216 bytes
Features	Flow control, auto-sensing per device, auto-negotiation, auto-uplink (auto MDI/MDI-X), store and forward, Link Fault Detection, QoS, D-Link Green Technology, fanless, metal housing, EEE, auto firmware update
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3az, IEEE 802.3bz
Status Indicators	Power, link/activity
Interfaces	5 x 10/100/1000 Base-T RJ-45 2 x 10/100/1000/2.5G RJ-45
Power Device	External power adapter

Power Consumption Operational	3.37 Watt
MTBF	944,277.78 hours
Compliant Standards	Plug and Play, FCC Class B certified, IC Class B, BSMI, RoHS, BSMI Class B, LVD, VCCI Class B, RCM Class B
Localisation	Europe
Width	14.5 cm
Depth	8.2 cm
Height	2.8 cm
Weight	295.2 g
Service & Support	Limited warranty - 2 years
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% RH
Min Storage Temperature	-10 °C
Max Storage Temperature	70 °C
Humidity Range Storage	5 - 95% RH